



Orientation	
	Size A3
Scale	1 : 100
XLBrng	96.00 deg.
Date	12/04/2011 /Mg
Ln/XL	0.00 deg.
Ln/AL	0.00 deg.

Load Diagrams		Load	Strength
Bending Moment	General	---	---
++++ (kNm) 20	Seismic	---	---
Shear Force	General	---	---
++++ (kN) 60	Seismic	---	---
Soil Pressure 50	Shear	---	---
++++ (kPa) 120	Bearing	---	---

Notes					Action		
1) Replace pole re SI's <1.0and low scan results at groundline test					1)		
2)					2)		
3)					3)		
4)					4)		


Tests	#	Target	Prt	Instruction	Comments	Requirements																																																						
																																																												
<table border="1"><thead><tr><th colspan="6">TPXScan</th></tr></thead><tbody><tr><td>Target (Pole)</td><td>PI</td><td></td><td></td><td></td><td></td></tr><tr><td>Level (Set'g+/-m)</td><td>0</td><td></td><td></td><td></td><td></td></tr><tr><td>Diam Original (mm)</td><td>230</td><td></td><td></td><td></td><td></td></tr><tr><td>Diam Residual (mm)</td><td>190</td><td></td><td></td><td></td><td></td></tr><tr><td>↑ ULS BM (kNm)</td><td>21</td><td></td><td></td><td></td><td></td></tr><tr><td>(%) of Original</td><td>27</td><td></td><td></td><td></td><td></td></tr><tr><td>← ULS BM (kNm)</td><td>28</td><td></td><td></td><td></td><td></td></tr><tr><td>(%) of Original</td><td>36</td><td></td><td></td><td></td><td></td></tr></tbody></table>							TPXScan						Target (Pole)	PI					Level (Set'g+/-m)	0					Diam Original (mm)	230					Diam Residual (mm)	190					↑ ULS BM (kNm)	21					(%) of Original	27					← ULS BM (kNm)	28					(%) of Original	36				
TPXScan																																																												
Target (Pole)	PI																																																											
Level (Set'g+/-m)	0																																																											
Diam Original (mm)	230																																																											
Diam Residual (mm)	190																																																											
↑ ULS BM (kNm)	21																																																											
(%) of Original	27																																																											
← ULS BM (kNm)	28																																																											
(%) of Original	36																																																											
<table border="1"><thead><tr><th colspan="6">Exposure</th></tr></thead><tbody><tr><td>Ref Site/Node</td><td>Prx</td><td>Wind (Pa)</td><td colspan="3">1,200.000</td></tr><tr><td>Distance (m)</td><td>0.00</td><td>Prx Snow (Pa)</td><td colspan="3">0.000</td></tr><tr><td>Bearing (deg)</td><td>0.00</td><td>Prx Ice mm</td><td>LC Mx</td><td>0.00</td><td>1.00</td></tr><tr><td>Terrain</td><td>Bush/Urban</td><td>T-Amb (deg C)</td><td colspan="3">15.00</td></tr><tr><td>Topography</td><td>Flat/Undulating</td><td>T-High</td><td>T-Low</td><td>50.00</td><td>0.00</td></tr><tr><td>Class   Slope</td><td>B1   0.00</td><td>Soil Class</td><td colspan="3">VFirm</td></tr><tr><td>Site Access</td><td colspan="5">Good Land Vehicle Access (Seasonal Weather Restrictions)</td></tr></tbody></table>							Exposure						Ref Site/Node	Prx	Wind (Pa)	1,200.000			Distance (m)	0.00	Prx Snow (Pa)	0.000			Bearing (deg)	0.00	Prx Ice mm	LC Mx	0.00	1.00	Terrain	Bush/Urban	T-Amb (deg C)	15.00			Topography	Flat/Undulating	T-High	T-Low	50.00	0.00	Class   Slope	B1   0.00	Soil Class	VFirm			Site Access	Good Land Vehicle Access (Seasonal Weather Restrictions)										
Exposure																																																												
Ref Site/Node	Prx	Wind (Pa)	1,200.000																																																									
Distance (m)	0.00	Prx Snow (Pa)	0.000																																																									
Bearing (deg)	0.00	Prx Ice mm	LC Mx	0.00	1.00																																																							
Terrain	Bush/Urban	T-Amb (deg C)	15.00																																																									
Topography	Flat/Undulating	T-High	T-Low	50.00	0.00																																																							
Class   Slope	B1   0.00	Soil Class	VFirm																																																									
Site Access	Good Land Vehicle Access (Seasonal Weather Restrictions)																																																											
<table border="1"><thead><tr><th colspan="3">Performance</th><th colspan="2">Load (SLS)</th><th>S.I (SLS)</th></tr></thead><tbody><tr><td>Classification</td><td>III</td><td>General (kN)</td><td>XLine ↓</td><td>3.84</td><td>0.71</td></tr><tr><td>Nom. Hght (m)</td><td>7.50</td><td>ALine →</td><td></td><td>3.16</td><td>1.04</td></tr><tr><td>Seismic Ftr (z)</td><td>1.00</td><td>Seismic (kN)</td><td>XLine ↑</td><td>0.22</td><td>7.71</td></tr><tr><td>Ductility Ftr (u)</td><td>1.00</td><td>ALine →</td><td></td><td>0.33</td><td>7.03</td></tr><tr><td>VPeriod XL (s)</td><td>3.61</td><td>Foundation (kPa)</td><td>Lateral ↑</td><td>109.03</td><td>1.32</td></tr><tr><td>VPeriod AL (s)</td><td>2.99</td><td>Bearing ⊗</td><td></td><td>142.22</td><td>2.53</td></tr><tr><td>Axial Load (kN)</td><td>4.55</td><td>Calc Model Rf</td><td colspan="3">LSE V2010 SLS/SICalc</td></tr></tbody></table>							Performance			Load (SLS)		S.I (SLS)	Classification	III	General (kN)	XLine ↓	3.84	0.71	Nom. Hght (m)	7.50	ALine →		3.16	1.04	Seismic Ftr (z)	1.00	Seismic (kN)	XLine ↑	0.22	7.71	Ductility Ftr (u)	1.00	ALine →		0.33	7.03	VPeriod XL (s)	3.61	Foundation (kPa)	Lateral ↑	109.03	1.32	VPeriod AL (s)	2.99	Bearing ⊗		142.22	2.53	Axial Load (kN)	4.55	Calc Model Rf	LSE V2010 SLS/SICalc								
Performance			Load (SLS)		S.I (SLS)																																																							
Classification	III	General (kN)	XLine ↓	3.84	0.71																																																							
Nom. Hght (m)	7.50	ALine →		3.16	1.04																																																							
Seismic Ftr (z)	1.00	Seismic (kN)	XLine ↑	0.22	7.71																																																							
Ductility Ftr (u)	1.00	ALine →		0.33	7.03																																																							
VPeriod XL (s)	3.61	Foundation (kPa)	Lateral ↑	109.03	1.32																																																							
VPeriod AL (s)	2.99	Bearing ⊗		142.22	2.53																																																							
Axial Load (kN)	4.55	Calc Model Rf	LSE V2010 SLS/SICalc																																																									
<table border="1"><thead><tr><th colspan="6">Structure Data Sheet (SI Calculations)</th></tr></thead><tbody><tr><td>Inspected</td><td>ABC01</td><td>9/04/2011</td><td rowspan="3">NZ Power Company North</td><td rowspan="3">Site Address 26 Orange Street</td><td>Zone</td><td>North</td></tr><tr><td>Modelled</td><td>ABC01</td><td>17/01/2012</td><td>Line</td><td>Northern</td></tr><tr><td>Reviewed</td><td></td><td></td><td>Site</td><td>12345</td></tr><tr><td colspan="5"></td><td>Ntwk#</td><td>1</td></tr><tr><td colspan="5"></td><td>Node#</td><td></td></tr></tbody></table>							Structure Data Sheet (SI Calculations)						Inspected	ABC01	9/04/2011	NZ Power Company North	Site Address 26 Orange Street	Zone	North	Modelled	ABC01	17/01/2012	Line	Northern	Reviewed			Site	12345						Ntwk#	1						Node#																		
Structure Data Sheet (SI Calculations)																																																												
Inspected	ABC01	9/04/2011	NZ Power Company North	Site Address 26 Orange Street	Zone	North																																																						
Modelled	ABC01	17/01/2012			Line	Northern																																																						
Reviewed					Site	12345																																																						
					Ntwk#	1																																																						
					Node#																																																							

S3



(9/04/2011)

(X)



100 mm